

## **DIESEL CLEAN BURN**

### TECHNICAL DATA SHEET

#### **DESCRIPTION**

Diesel Clean Burn reduces soot emissions and cleans the DPF, turbo and EGR valve. The catalytic chemistry enables the DPF regeneration process to occur at a lower temperature allowing the vehicle to regenerate more frequently, even when driving conditions are not suitable to enable a normal regeneration phase. Adding Diesel Clean Burn to the fuel, facilitates a catalytic reaction which reduces the carbon deposit decomposition temperature to 450°C, resulting in more frequent burn-off at lower driving speeds. This prevents the problem of DPF blocking in stop/start city driving conditions. Similarly, the exhaust side of the Turbo as well as the EGR valve benefit from the reduced carbon.

#### **KEY BENEFITS**

- Removes carbon and soot particles from the DPF through catalytic combustion of contaminants.
- Cleans the Turbo and maintains EGR valve by reducing carbon deposits.
- Optimizes combustion and lowers fuel consumption.

#### **APPLICATIONS**

- Add to tank to regenerate DPF.
- Use every 5000km to prevent DPF clogging.
- Clean exhaust turbo fan to reduce turbo lag.
- Maintain efficient EGR valve operation.
- Especially suited for stop/ start city driving.

#### **DIRECTIONS FOR USE**

- Add contents to diesel tank every 5000km or as required.
- Treats 70L of diesel.

#### **PACK SIZES**

12 x 375ml

#### **PHYSICAL SPECIFICATIONS**

Appearance	Liquid
Density @20°C	0.832 kg/dm <sup>3</sup>
Colour	Blue
Flash point	71 °C
Odour	Characteristic

#### **HEALTH & SAFETY DATA**

Material Safety Data Sheets are available from the company.

## **SHELF LIFE**

Whilst Fast products are formulated to have as long a shelf life as possible, other factors do influence their actual useful life. Handling and storage conditions can cause packaging deterioration which could render the product unfit for further use. From time to time products are superseded by upgraded products and/or changed formulations and older products will no longer have the same performance level or be compatible with latest technology being introduced into equipment. It is therefore the responsibility of the purchaser of the product to ensure proper storage conditions, stock rotation and timely usage to prevent products from becoming unsuitable for use.

## **EXPIRY DATE**

3 Years from manufacture date.

## **DISCLAIMER**

The results displayed in this data sheet have been acquired using the latest revision of the methods indicated unless stated otherwise and may not be reproduced (except in full) without the written approval of Fast Racing Fuels. This test report is computer generated so a signature/stamp is not necessary.



### **Performance**

Formulated for specific applications to ensure optimum performance.



### **Consistency**

All our products offer industry leading levels of consistency and repeatability.



### **Quality**

We pride ourselves on offering the highest standard of quality in each of our products.