

## **SUMMER ICE COOLANT ANTIFREEZE**

### TECHNICAL DATA SHEET

#### **DESCRIPTION**

A 40% pre-mixed high performance inorganic coolant /antifreeze package for old and modern vehicles. Made from the finest Euro spec glycols, anti corrosion and anti foam agents to provide superior protection. Meets ASTM D3306/D4985; SAE J-1034; British & Fed. Standards.

#### **KEY BENEFITS**

- Protects cooling system from fouling.
- Prevents corrosion.
- Anti-foaming agent prevents cavitation and pitting.
- Freezing Point: 25°C (ASTM D1177).

#### **ADVANTAGES TO THE USER**

- Suitable for all radiator types.
- Ready to use as complete replacement or top up.
- Maintains correct operating temperature.
- Available in 1L or 2L.

#### **DIRECTIONS FOR USE**

- Add contents to the radiator without diluting. We recommend using Fast Performance Radiator Flush before changing coolant at vehicle manufacturer specified service intervals.

#### **PACK SIZES**

|     |              |
|-----|--------------|
| 510 | 12 x 1 Litre |
| 515 | 6 x 2 Litre  |

#### **PHYSICAL SPECIFICATIONS**

|               |                         |
|---------------|-------------------------|
| Appearance    | Clear turquoise liquid  |
| Density @20°C | 1.02 kg/dm <sup>3</sup> |
| Flash point   | N/A                     |
| Odour         | Characteristic          |

#### **HEALTH & SAFETY DATA**

Material Safety Data Sheets are available from the company.

## **SHELF LIFE**

Whilst Fast products are formulated to have as long a shelf life as possible, other factors do influence their actual useful life. Handling and storage conditions can cause packaging deterioration which could render the product unfit for further use. From time to time products are superseded by upgraded products and/or changed formulations and older products will no longer have the same performance level or be compatible with latest technology being introduced into equipment. It is therefore the responsibility of the purchaser of the product to ensure proper storage conditions, stock rotation and timely usage to prevent products from becoming unsuitable for use.

## **EXPIRY DATE**

5 Years from manufacture date.

## **DISCLAIMER**

The results displayed in this data sheet have been acquired using the latest revision of the methods indicated unless stated otherwise and may not be reproduced (except in full) without the written approval of Fast Racing Fuels. This test report is computer generated so a signature/stamp is not necessary.



### **Performance**

Formulated for specific applications to ensure optimum performance.



### **Consistency**

All our products offer industry leading levels of consistency and repeatability.



### **Quality**

We pride ourselves on offering the highest standard of quality in each of our products.