

IGNITE E50

TECHNICAL DATA SHEET

DESCRIPTION

With a blend of 50% Ethanol E100 and 50% Motorsport 98 Unleaded, It is perfect for those mid-range horsepower levels, crate motor applications. If you looking for ultimate performance and consistency for optimum tuning this will be your choice can be classed as the lowest and cleanest emission performance unleaded fuel developed in SA and components approved by the EU REACH Legislation.

REFERENCE NO.

170572A

DATE

16-09-2024

BATCH NO.

060924A

INSTRUCTIONS

(DIRECT-TO-TANK)

S No.	Parameters	Unit	Typical Results	Testing Method
1	Appearance		Clear Liquid	Visual
2	Colour		Light Green	ASTM D1500
3	Specific Density @ 20°C		0.7782g/cm ³	ASTM D1298
4	Total Purity By GLC	%	50	GLC In-House Method
5	Flash Point	°C	39	ASTM D93
6	Water Content	PPM	0.01	ASTM D6304
7	RON	cST	106	ASTM 2699
8	MON		89	ASTM D2700
9	R+M/2		99.5	
10	Oxygen Content	%m/m	4.5	ASTM D4815



11	Nitrogen	%m/m	0.2	ASTM D5453
12	Benzene	%m/m	5	ASTM D5443
13	RVP	Кра	7.0	ASTM D5443
14	Lead Content	gPb/l	0.004	ASTM D3348
15	Induction Period	minutes	370	ASTM D525
16	Existing Gum	Mg/100ml	3	ASTM D381
17	Sulphur	%m/m	0.01	ASTM D5453
18	Copper Corrosion	rating	1	ASTM D130
19	Distillation 50%			
20	Distillation 90%			
21	Distillation FBP			
22	Residue			
23	Conductivity @ 20oC			

DISCLAIMER

The results displayed in this data sheet have been acquired using the latest revision of the methods indicated unless stated otherwise and may not be reproduced (except in full) without the written approval of Fast Racing Fuels. This test report is computer generated so a signature/stamp is not necessary.



Performance

Formulated for specific applications to ensure optimum performance.



Consistency

All our products offer industry leading levels of consistency and repeatability.



Quality

We pride ourselves on offering the highest standard of quality in each of our products.