

## IGNITE E95

### TECHNICAL DATA SHEET

#### DESCRIPTION

IGNITE E95 Ethanol only available ethanol in South Africa with 98% Ethanol Purity. Product has been denatured with Valve Seat Recession additives to prevent deposit build up on intake valves and corrosion inhibitors. IGNITE E95 IS treated with a M2 Upper Lubricant which protects the investment in your ethanol powered engine, it protects valves and guides, protects aluminium fuel system parts and protects cylinder walls and also treated with a fuel stabiliser which is a three year fuel stabiliser which eliminates ethanol fuel problems, protects and prevents need for repairs, extends engine life and reduces heat. Best suited for flex fuel systems designed for Ethanol blends. Consistent blend with no variations perfect for calibrations engineers who require consistency for fine tuning. Shelf life is in excess of 6 months

#### REFERENCE NO.

42509C

#### DATE

16-09-2024

#### BATCH NO.

07092024A

#### INSTRUCTIONS

(DIRECT-TO-TANK)

S No.	Parameters	Unit	Typical Results	Testing Method
1	Colour	----	Clear Liquid	Visual
2	RON	cST	113	ASTM 2699
3	MON	----	98	ASTM 2700
4	R+M/2	----	105	----
5	Density	----	0.771	ASTM 1298

## DISCLAIMER

The results displayed in this data sheet have been acquired using the latest revision of the methods indicated unless stated otherwise and may not be reproduced (except in full) without the written approval of Fast Racing Fuels. This test report is computer generated so a signature/stamp is not necessary.



### Performance

Formulated for specific applications to ensure optimum performance.



### Consistency

All our products offer industry leading levels of consistency and repeatability.



### Quality

We pride ourselves on offering the highest standard of quality in each of our products.